

Batterie V-Mount Li-ion 96Wh 2 sorties D-tap&USB



Codes

Reference: DUO-C98

Résumé

La DUO-C98 est une batterie Li-Ion compacte haute capacité avec de multiples sorties parfaite pour les stabilisateurs de poing et les configurations nécessitant un transport aérien (<100Wh). La DUO-C98 est équipée de deux D-Taps et une sortie USB pour les accessoires.

Descriptif

96Wh capacity 1.5 inches in depth Compact high capacity IATA friendly (<100Wh) Lithium Ion battery (1.37lbs) Capable of handling up to 6.3A/70W loads (1) 50W D-Tap Advanced output (unregulated) - D-Tap Output with the added ability to charge battery using low-cost D-Tap Charger (coming soon from IDX) (1) 50W D-Tap output (unregulated) (1) 5V USB output (auto shut off after 30 minutes of inactivity) 5 Power Indicator LEDs Battery circuit protection ensures the DUO-C98 is fully protected against common causes of battery misuse, guarding against over charge, over discharge, over current and exposure to high temperatures The highest grade Lithium Ion cells are used to ensure the DUO-C98 is one of the most reliable batteries on the market 11V auto cut-off prevents over-discharging (while a load is applied) Unrestricted amount of spare DUO-C98 batteries allowed for carry-on airline baggage under IATA regulations Fully compatible with all ENDURA V-Mount chargers and accessories Environmentally friendly and recyclable Battery Capacity 14.4V, 6.6Ah, 96Wh* Max. Output Voltage 16.8V DC Nominal Voltage 14.4V DC Maximum Discharge Current 10A D-Tap 4.1A / 50W each USB 2.3A / 11.5W End Voltage 11V Battery Protection Reverse charge, Over charge, Over discharge, Over current, Temperature protection Ambient Temperature To charge: 0°C ~ 40°C (10°C ~ 30°C recommended) To discharge: -20°C ~ 45°C (10°C ~ 40°C recommended) To store: -20°C ~ 50°C (one month) Dimensions 97(W)x146(H)x39(D)mm