

# CiNX 3 Solo 100 3 Sections Fibre de Carbone



## Description brève du produit :

Le système 3802 CiNX 3 Solo 100 3 Sections Fibre de Carbone est un système léger et robuste, conçu pour les professionnels du cinéma qui recherchent une solution de support polyvalente et performante.

## Codes produits :

Référence 3802

EAN13 : -

CUP : -

## Description du produit :

- Fluid drag system with smooth start and soft stop technology.
- 5 selectable positions of fluid pan and tilt drag + 0.
- 16 positions of counterbalance.
- Perfect for payload range from 1kg (2.2lbs) up to 19kg (41.8lbs).
- Precise floating pan-tilt calliper locks ensure bounce free on-off performance.
- Integrated 100mm bowl.
- Lightweight carbon fibre legs.
- 3-position leg angle locking - no spreader.
- 3-stage rapid leg lock extension.
- 3 years warranty.

The CiNX 3 Solo 100 3 Stage (carbon fibre) is a lightweight and durable system, packed with features, all designed to meet the needs of cinematographers. For today's versatile shooter.

The sideload platform enables rapid deployment of countless sizes of camera rigs as well as extended camera plate range of movement for balancing front heavy setups.

Featuring a wide payload range, precision fluid drag and Miller's innovative 16 position CB Plus™ counterbalance system, CiNX 3 delivers the flexibility, speed of set up and accuracy of shot, professionals expect and demand.

With a payload range 1-19kg (2.2-41.8lbs) and 5 + 0 selectable pan-tilt fluid drag positions makes the CiNX 3 ideal for cinematographers with lighter rigs, requiring lighter pan, and tilt drag.

The Solo 100 3-stage tripod uses the most advanced carbon/basalt fibre tubing for the highest stiffness to weight ratios there is, high strength magnesium and die cast alloy components are incorporated to provide an ultra-light tripod.

With an ultra-low minimum height of 422mm (16.6") to the heights of 2072mm (81.5") safely with no spreader and easy ball levelling you are guaranteed outstanding stable images from any angle across any terrain.

Gamme de charge utile 1-19kg (2.2-41.8lbs) Poids 8.0kg (17.6lbs) Hauteur 422-2072mm (16.6-81.5") Longueur de transport 860mm (33.8") Positions de contrepoids 16 selectable positions Pan Tilt Drag 5 selectable fluid drag positions + 0 Verrouillage panoramique Positive lock calliper brake system Plage d'inclinaison +90° / -75° Gamme Pan 360° Plateforme camera Side loading quick release camera plate (Arri type) Portee coulissante 150mm (5.9") Base de montage Ø100mm (3.9") ball levelling Hauteur au-dessus du bol 202mm (8.0") MB 200mm (7.9") Commandes eclairees Bubble level, pan-tilt drag controls Poignee panoramique Telescopic 390-590mm (15.4-23.2") Ecart de temperature -40° to +65°C (-40° to +150°F) Extension des jambes 3-stage Type de verrouillage Concentric Rapid Lock Materiel de jambe Carbon fibre Composants 1103 CiNX 3 Fluid Head 1505 Solo 100 3-stage tripod (carbon fibre) 1520 Solo Shoulder Strap Aircell 3502 Softcase 2 Stage