

# CiNX 5 HDC 100 1 Section Alliage Triangle intermédiaire



## Description brève du produit :

Le système 3834 CiNX 5 HDC 100 1 Section Alliage Triangle intermédiaire est un système léger et robuste, conçu pour les professionnels du cinéma qui recherchent une solution de support polyvalente et performante.

## Codes produits :

Référence 3834

EAN13 : -

CUP : -

## Description du produit :

- Fluid drag system with smooth start and soft stop technology.
- 7 selectable positions of fluid pan and tilt drag + 0.
- 16 positions of counterbalance.
- Perfect for payload range from 2-21kg (4.4-46.2lbs).
- Precise floating pan-tilt calliper locks ensure bounce free on-off performance.
- Integrated 100mm bowl.
- 1-stage rotary lock leg extension.
- Heavy duty black anodised alloy tubing.
- Integrated stainless steel spikes.
- Comes with mid-level spreader.
- 3 years warranty.

The CiNX 5 HDC 100 1 Stage (alloy) is a lightweight and durable system, packed with features, all designed to meet the needs of cinematographers.

The sideload platform enables rapid deployment of countless sizes of camera rigs as well as extended camera plate range of movement for balancing front heavy setups.

Featuring a wide payload range, precision fluid drag and Miller's innovative 16 position CB Plus™ counterbalance system, CiNX 5 delivers the flexibility, speed of set up and accuracy of shot, professionals expect and demand. Perfect for lighter rigs, requiring more positions of pan, and tilt drag.

With a payload range 2-21kg (4.4-46.2lbs) and 7 + 0 selectable pan-tilt fluid drag positions makes the CiNX 5 ideal for cinematographers with lighter rigs, requiring lighter pan, and tilt drag.

The HDC 100 1-stage tripod incorporates a 100mm bowl, metal rotary leg locks and comes with the 993 above ground spreader.

HDC series tripods are designed with stability in mind, uses heavy duty 24mm alloy tubing coupled with the Miller 100mm bowl, to make a very stable platform. No matter where your work takes you, the HDC tripod series performs in extreme climates and terrains every time.

Quick action rotary screw type leg locks allow for maximum lock off performance without need for maintenance.

Gamme de charge utile 2-21kg (4.4-46.2lbs) Poids 12.0kg (26.4lbs) Hauteur 972-1739mm (38.2-68.0") Longueur de transport 1108mm (43.6") Positions de contrepoids 16 selectable positions Pan Tilt Drag 7 selectable fluid drag positions + 0 Verrouillage panoramique Positive lock calliper brake system Plage d'inclinaison +90° / -75° Gamme Pan 360° Plateforme camera Side loading quick release camera plate (Arri type) Portee coulissante 150mm (5.9") Base de montage Ø100mm (3.9") ball levelling Hauteur au-dessus du bol 202mm (8.0") MB 200mm (7.9") Commandes eclairees Bubble level, pan-tilt drag controls Poignee panoramique Telescopic 390-590mm (15.4-23.2") Ecart de temperature -40° to +65°C (-40° to +150°F) Extension des jambes 1-stage Type de verrouillage Quick action rotary lock Materiel de jambe Alloy Composants 1105 CiNX 5 Fluid Head 698 Pan Handle HD Telescopic with clamp 2121 HDC 100mm 1-stage tripod (alloy) 993 Mid-level spreader 3615 Smart Case (long)