

# CiNX 7 HDC 150 1 Section Alliage Triangle de sol



## Description brève du produit :

Le système 3876 CiNX 7 HDC 150 1 Section Alliage Triangle de sol est un système léger et robuste, conçu pour les professionnels du cinéma qui recherchent une solution de support polyvalente et performante.

## Codes produits :

Référence 3876

EAN13 : -

CUP : -

## Description du produit :

- Fluid drag system with smooth start and soft stop technology.
- 7 selectable positions of fluid pan and tilt drag + 0.
- 16 positions of counterbalance.
- Perfect for payload range from 6-25kg (13.2-55lbs).
- Precise floating pan-tilt calliper locks ensure bounce free on-off performance.
- Integrated 150mm bowl.
- 1-stage rotary lock leg extension.
- Heavy duty black anodised alloy tubing.
- Integrated stainless steel spikes.
- Comes with HDC Ground spreader.
- 3 years warranty.

The CiNX 7 HDC 150 1 Stage (alloy) is a lightweight and durable system, packed with features, all designed to meet the needs of cinematographers.

The sideload platform enables rapid deployment of countless sizes of camera rigs as well as extended camera plate range of movement for balancing front heavy setups.

Featuring a wide payload range, precision fluid drag and Miller's innovative 16 position CB Plus™ counterbalance system, CiNX 7 delivers the flexibility, speed of set up and accuracy of shot, professionals expect and demand. The ultimate fluid head for heavier rigs, requiring more positions of pan, and tilt drag.

With a payload range 6-25kg (13.2-55lbs) and 7 + 0 selectable pan-tilt fluid drag positions makes the CiNX 7 ideal for cinematographers with lighter rigs, requiring lighter pan, and tilt drag.

The 2115G HDC tripod is specifically built for cinematographers and outside broadcasters who demand the highest levels of stability, low torsional distortion, even at maximum drag, and heavy load strength from their tripods.

The HDC 150 1-stage tripod incorporates a 150mm bowl, metal rotary leg locks and is best suited to the all metal 2130 HDC on ground spreader.

Quick action rotary screw type leg locks allow for maximum lock off performance without need for maintenance.

Gamme de charge utile 6-25kg (13.2-55lbs) Poids 12.6kg (27.8lbs) Hauteur 929-1741mm (36.1-68.5") Longueur de transport 1138mm (44.8") Positions de contrepoids 16 selectable positions Pan Tilt Drag 7 selectable fluid drag positions + 0 Verrouillage panoramique Positive lock calliper brake system Plage d'inclinaison +90° / -75° Gamme Pan 360° Plateforme camera Side loading quick release camera plate (Arri type) Portee coulissante 150mm (5.9") Base de montage Ø150mm (5.9") ball levelling Hauteur au-dessus du bol 202mm (8.0") MB 200mm (7.9") Commandes éclairées Bubble level, pan-tilt drag controls Poignée panoramique Telescopique 390-590mm (15.4-23.2") Ecart de température -40° to +65°C (-40° to +150°F) Extension des jambes 1-stage Type de verrouillage Quick action rotary lock Matériel de jambe Alloy Composants 1107 CiNX 7 Fluid Head 1295 D150 Claw ball level 698 Pan Handle HD Telescopique with clamp 2115G HDC 150 1-stage tripod (alloy) 2130 Ground Spreader 3615 Smart Case (long)