

CiNX 7 HDC 150 1 Section Alliage Triangle intermédiaire



Description brève du produit :

Le système 3878 CiNX 7 HDC 150 1 Section Alliage Triangle intermédiaire est un système léger et robuste, conçu pour les professionnels du cinéma qui recherchent une solution de support polyvalente et performante.

Codes produits :

Référence 3878

EAN13 : -

CUP : -

Description du produit :

- Fluid drag system with smooth start and soft stop technology.
- 7 selectable positions of fluid pan and tilt drag + 0.
- 16 positions of counterbalance.
- Perfect for payload range from 6-25kg (13.2-55lbs).
- Precise floating pan-tilt calliper locks ensure bounce free on-off performance.
- Integrated 150mm bowl.
- 1-stage rotary lock leg extension.
- Heavy duty black anodised alloy tubing.
- Integrated stainless steel spikes.
- Comes with mid-level spreader.
- 3 years warranty.

The CiNX 7 HDC 150 1 Stage (alloy) is a lightweight and durable system, packed with features, all designed to meet the needs of cinematographers.

The sideload platform enables rapid deployment of countless sizes of camera rigs as well as extended camera plate range of movement for balancing front heavy setups.

Featuring a wide payload range, precision fluid drag and Miller's innovative 16 position CB Plus™ counterbalance system, CiNX 7 delivers the flexibility, speed of set up and accuracy of shot, professionals expect and demand. The ultimate fluid head for heavier rigs, requiring more positions of pan, and tilt drag.

With a payload range 6-25kg (13.2-55lbs) and 7 + 0 selectable pan-tilt fluid drag positions makes the CiNX 7 ideal for cinematographers with lighter rigs, requiring lighter pan, and tilt drag.

The 2115 HDC tripod is specifically built for cinematographers and outside broadcasters who demand the highest levels of stability, low torsional distortion, even at maximum drag, and heavy load strength from their tripods.

The HDC 150 1-stage tripod incorporates a 150mm bowl, metal rotary leg locks and is best suited to the 993 above ground spreader.

Quick action rotary screw type leg locks allow for maximum lock off performance without need for maintenance.

Gamme de charge utile 6-25kg (13.2-55lbs) Poids 12.2kg (26.9lbs) Hauteur 992-1742mm (39.0-68.5") Longueur de transport 1108mm (43.6") Positions de contrepoids 16 selectable positions Pan Tilt Drag 7 selectable fluid drag positions + 0 Verrouillage panoramique Positive lock calliper brake system Plage d'inclinaison +90° / -75° Gamme Pan 360° Plateforme camera Side loading quick release camera plate (Arri type) Portee coulissante 150mm (5.9") Base de montage Ø150mm (5.9") ball levelling Hauteur au-dessus du bol 202mm (8.0") MB 200mm (7.9") Commandes eclairees Bubble level, pan-tilt drag controls Poignee panoramique Telescopic 390-590mm (15.4-23.2") Ecart de temperature -40° to +65°C (-40° to +150°F) Extension des jambes 1-stage Type de verrouillage Quick action rotary lock Materiel de jambe Alloy Composants 1107 CiNX 7 Fluid Head 1295 D150 Claw ball level 698 Pan Handle HD Telescopic with clamp 2115 HDC 150 1-stage tripod (alloy) 993 Mid-level spreader 3615 Smart Case (long)