

# IDX Kit comprenant: 2 batteries NP-9X + 1 chargeur JL-2Plus



## Description brève du produit :

Kit comprenant: 2 batteries NP-9X + 1 chargeur JL-2Plus

## Codes produits :

Référence NP-L2X

EAN13 : -

CUP : -

## Description du produit :

### Chargeur JL-2Plus:

Input Voltage AC 100-240V 50/60Hz

Power Consumption 140VA Max.

Quick Charge Current - Li-ion : 2.3 A - Ni-CD/Ni-MH : 1.9A

DC Output 60W max.

Operating Temperature 0°C ~ 40°C

Dimensions 150(W) x 70(H) x 212(D) mm

Weight 798 grams approx.

**Batterie NP-9X:**

Capacity: 96Wh (14.4V/ 6.6Ah)

Max Output Voltage: 16.8V DC

Nominal Voltage: 14.4V DC

Max Discharge Current: 4.6A‡ ( total of main connector and d-taps )

End Voltage: 11V

D-Tap: 50W each

D-Tap Advanced: Compatible only with IDX VL-DT1 charger

Battery Protection: Over charge, Over discharge, Over current, Thermal protection

Ambient Temperature: To charge: 32°F ~ 104°F (50°F ~ 86°F recommended)

To discharge: -4°F ~ 113°F (50°F ~ 104°F recommended)

To store: -4°F ~ 104°F

Dimensions: 7.26(W) x 2.80(H) x 0.97(D) inches

Weight: 1.15 lbs approx.

Included Accessories: Terminal cover

‡ may vary depending on the operating temperature